

<b>Description</b>	<b>OmniExtender GXPoE+/S and GXHPoE/S</b> 10/100/1000BASE-T Ethernet PoE/PD to PoE/PSE Extenders	
<b>Standard Compliances</b>	IEEE 802.3, IEEE 802.3at PoE+, High-Power 60W PoE	
<b>Environmental</b>	REACH, RoHS and WEEE	
<b>PoE/PD Mode</b>	IEEE Alternate A (Alt A)	
<b>Frame Size</b>	Up to 10,240 bytes	
<b>Port Types</b>	Copper:	10/100/1000BASE-T (RJ-45)
<b>Cable Types</b>	Copper:	EIA/TIA 568A/B, Cat 5 UTP and higher
<b>Power Requirements</b>	PoE/PD (input):	+/-42.5 to +/-57VDC (per IEEE)
	PoE/PSE (output):	+/-50 to +/-57VDC (per IEEE)と)
		56VDC (typical)
<b>Dimensions</b>	W : 3.8 "x D : 4.8" x H : 1.0 "	
	L : 96.52 mm x B : 121.92 mm x H : 25.4 mm	
<b>Weight</b>	0.82 lbs; 372 grams	
<b>Operating Temperature</b>	Commercial:	0~50°C
	Wide:	-40~ + 60°C
<b>Humidity</b>	5% to 95% (non-condensing)	
<b>Altitude</b>	-100m to 4,000m (operational)	
<b>MTBF (hrs)</b>	1xPD Port+1xPSE Port:	375,000
	1xPD Port+2xPSE Ports:	317,000
<b>Warranty</b>	Lifetime warranty with 24/7/365 free Technical Support	