

<b>Description</b>	<b>miConverter GX/T PoE/D</b> <b>10/100/1000BASE-T to 100/1000BASE-X Fiber Converter Powered by PoE</b>	
<b>Standard</b>	IEEE 802.3	
<b>Compliances Regulatory</b>	UL, CE, FCC Class A, RoHS, REACH, WEEE	
<b>Compliances</b>		
<b>Frame Size</b>	Up to 10,240 bytes	
<b>Port Types</b>	Copper:	10/100 / 1000BASE-T (RJ-45)
	Fiber:	100BASE-X (SFP)
		1000BASE-X (ST, SC, LC, SFP)
<b>Cable Types</b>	Copper:	EIA/TIA 568A/B, Cat 5 UTP and higher
	Fiber:	Multimode: 50/125µm, 62.5/125µm
		Single-mode: 9/125µm
<b>AC Power Requirements</b>	AC/DC Adapter:	100 - 240VAC/50 - 60Hz
		0.03 @ 120VAC (max)
<b>DC Power Requirements</b>	DC Input:	8.0 to 60.0VDC
	(AC/DC Adapter)	0.278A @ 9VDC
		2.5mm Barrel Connector
	DC Input:	8.0~60.0VDC
	(Terminal Connector)	0.278A @ 9VDC
		2-Pin Terminal (non-isolated)
	DC Input:	44 - 57VDC, 0.05A @ 48VDC (typical)
	(PoE)	RJ-45 (Alternative A & B)
<b>Dimensions W x D x H</b>	Standalone:	W : 1.71" x D : 4.10" x H : 0.84" (L : 43.4 mm x B : 104.1 mm x H : 21.3 mm)
	Standalone	W : 2.41" x D : 4.10" x H : 0.84"
	w/Integrated Brackets	(L : 61.2 mm x B : 104.1 mm x H : 21.3 mm)
<b>Weight</b>	Module Only:	4 oz. (113.4 grams)
	With AC/DC Adapter:	12 oz. (340.2 grams)
<b>Temperature</b>	Commercial:	0~50°C
	Wide:	-40~60°C、-20°CACコールドスタート
	Storage:	-50~85°C
<b>Humidity</b>	5% to 95% (non-condensing)	
<b>Altitude</b>	-100m to 4,000m (operational)	
<b>MTBF (hrs)</b>	Module Only:	859,588
	With AC/DC Adapter:	102,249
<b>Warranty</b>	Lifetime warranty with 24/7/365 free Technical Support	